

Trillion Colorant SB Black - 54202

ICP Construction

Version No: 1.1 Safety Data Sheet according to OSHA HazCom Standard (2012) requirements Issue Date: **06/18/2018** Print Date: **06/18/2018** S.GHS.USA.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Trillion Colorant SB Black - 54202
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Colorant
--------------------------	----------

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction
Address	150 Dascomb Road Andover MA United States
Telephone	978-623-9980
Fax	Not Available
Website	http://www.icp-construction.com/
Email	Not Available

Emergency phone number

Association / Organisation	Chemtel	
Emergency telephone numbers	1-800-255-3924	
Other emergency telephone numbers	1-813-248-0585	

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Skin Sensitizer Category 1

Label elements

Hazard pictogram(s)



SIGNAL WORD

WARNING

Hazard statement(s)

H317 May cause an allergic skin reaction.

Hazard(s) not otherwise specified

Not Applicable

Precautionary statement(s) General

Page 2 of 8

Trillion Colorant SB Black - 54202

Issue Date: **06/18/2018** Print Date: **06/18/2018**

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.

Precautionary statement(s) Prevention

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P261	Avoid breathing mist/vapours/spray.

Precautionary statement(s) Response

	_ •
P363	Wash contaminated clothing before reuse.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
1333-86-4	20-40	carbon black
14807-96-6	2.5-10	talc

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with eyes: • Wash out immediately with water. • If irritation continues, seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

▶ Sand, dry powder extinguishers or other inerts should be used to smother dust fires.

At temperatures above 1500 C, carbon, graphite or graphene reacts with substances containing oxygen, including water and carbon dioxide. In case of intensely hot fires sand should be used to cover and isolate these materials.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates oxidising acids chlorine bleaches pool chlorine etc. as ignition may result	

Special protective equipment and precautions for fire-fighters

Special protective equipment and precautions for fire-fighters		and precautions for fire-fighters
	Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus.
	Fire/Explosion Hazard	 ▶ Combustible. ▶ Slight fire hazard when exposed to heat or flame. Combustion products include: carbon dioxide (CO2)

Chemwatch: 9-552493 Page 3 of 8

Version No: 1.1

Trillion Colorant SB Black - 54202

Issue Date: 06/18/2018 Print Date: 06/18/2018

silicon dioxide (SiO2)

other pyrolysis products typical of burning organic material.

May emit corrosive fumes.

A fire in bulk finely divided carbon may not be obviously visible unless the material is disturbed and sparks appear. A straw broom may be useful to produce the disturbance.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 ▶ Remove all ignition sources. ▶ Clean up all spills immediately.
Major Spills	Moderate hazard. ► Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

i recautions for sale mananing	,
Safe handling	NOTE: Wet, activated carbon removes oxygen from the air thus producing a severe hazard to workers inside carbon vessels and in enclosed or confined spaces where activated carbons might accumulate. Before entry to such areas, sampling and test procedures for low oxygen levels should be undertaken; control conditions should be established to ensure the availability of adequate oxygen supply. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. DO NOT allow clothing wet with material to stay in contact with skin
Other information	Carbon and charcoal may be stabilised for storage and transport, without moistening, by treatment with hot air at 50 deg. C Store in original containers. Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	For carbon powders: Avoid oxidising agents, reducing agents. Reaction with finely divided metals, bromates, chlorates, chloramine monoxide, dichlorine oxide, iodates, metal nitrates, oxygen difluoride, peroxyformic acid, peroxyfuroic acid and trioxygen difluoride may result in an exotherm with ignition or explosion. Activated carbon, when exposed to air, represents a potential fire hazard due to a high surface area and adsorptive capacity. Freshly prepared material may ignite spontaneously in the presence of air especially at high humidity.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	carbon black	Acetylene black, Channel black, Furnace black, Lamp black, Thermal black	3.5 mg/m3	Not Available	Not Available	Ca See Appendix A See Appendix C
US ACGIH Threshold Limit Values (TLV)	carbon black	Carbon black	3 mg/m3	Not Available	Not Available	TLV® Basis: Bronchitis
US OSHA Permissible Exposure Levels (PELs) - Table Z1	carbon black	Carbon black	3.5 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	talc	Massive talc, Soapstone silicate, Steatite	6 (total), 3 (resp) mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	talc	Hydrous magnesium silicate, Steatite talc	2 (resp) mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Soapstone	20 mppcf	Not Available	Not Available	(Name ((less than 1% crystalline silica)))
US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Talc	Not Available	Not Available	Not Available	(Name ((less than 1% crystalline silica); (containing asbestos) Use asbestos limit))

Chemwatch: **9-552493** Page **4** of **8**

Version No: 1.1

Trillion Colorant SB Black - 54202

Page 4 of 8 Issue Date: 06/18/2018
Print Date: 06/18/2018

US OSHA Permissible Exposure Levels (PELs) - Table Z3	talc	Silicates: Talc	20 mppcf	Not Available	Not Available	(Name ((less than 1% crystalline silica); (not containing asbestos))); (TWA mppcf (((c) Containing less than 1% quartz; if 1% quartz or more, use quartz limit.)))
US ACGIH Threshold Limit Values (TLV)	talc	Talc - Containing no asbestos fibers	2 mg/m3	Not Available	Not Available	TLV® Basis: Pulm fibrosis; pulm func
US ACGIH Threshold Limit Values (TLV)	talc	Talc - Containing asbestos fibers	Not Available	Not Available	Not Available	TLV® Basis: Use Asbestos TLV®
US OSHA Permissible Exposure Levels (PELs) - Table Z1	talc	Silicates (less than 1% crystalline silica): Talc (containing no asbestos), respirable dust	Not Available	Not Available	Not Available	See Table Z-3
US OSHA Permissible Exposure Levels (PELs) - Table Z1	talc	Silicates (less than 1% crystalline silica): Talc (containing asbestos); use asbestos limit	Not Available	Not Available	Not Available	see 29 CFR 1910.1001; See Table Z-3

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
carbon black	Carbon black	9 mg/m3	99 mg/m3	590 mg/m3
talc	Talc	6 mg/m3	66 mg/m3	400 mg/m3

Ingredient	Original IDLH	Revised IDLH
carbon black	1750 mg/m3	Not Available
talc	1000 mg/m3	Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Exhaust ventilation should be designed to prevent accumulation and recirculation in the workplace and safely remove carbon black from the air.

Note: Wet, activated carbon removes oxygen from the air and thus presents a severe hazard to workers inside carbon vessels and enclosed or confined spaces.

Personal protection









Eye and face protection

- ► Safety glasses with side shields
- Chemical goggles

Skin protection

See Hand protection below

- ► Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

Hands/feet protection

► The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Body protection

See Other protection below

Other protection

OverallsP.V.C.

Respiratory protection

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

• •			
Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available

Chemwatch: 9-552493 Page 5 of 8

Version No: 1.1

Trillion Colorant SB Black - 54202

Issue Date: 06/18/2018 Print Date: 06/18/2018

Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Impurities found in carbons, including iodine, can be toxic. Carbon dusts in the air may cause irritation of the mucous membranes, eyes and skin.			
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Ingestion of finely divided carbon may produce gagging and constipation. Aspiration does not appear to be a concern as the material is generally regarded as inert and is often used as a food additive.			
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Еуе	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Eyes exposed to carbon particulates may be liable to irritation and burning. These can remain in the eye causing inflammation lasting weeks, and can cause permanent dark dotty discolouration.			
Chronic	Skin contact with the material is more likely to cau There has been concern that this material can cau			• •
Trillion Colorant SB Black - 54202	TOXICITY IRRITATION Not Available Not Available			
carbon black	TOXICITY IRRITATION			
talc	TOXICITY IRRITATION Not Available Skin (human): 0.3 mg/3d-l mild			
Legend:	Value obtained from Europe ECHA Registered data extracted from RTECS - Register of Toxic E.			turer's SDS. Unless otherwise specified

Trillion Colorant SB Black - 54202	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema.
CARBON BLACK	WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans. Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported
TALC	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. The overuse of talc in nursing infants has resulted in respiratory damage causing fluid in the lungs and lung inflammation which may lead to death within hours of inhalation.

Chemwatch: 9-552493 Page 6 of 8
Version No: 1.1

Trillion Colorant SB Black - 54202

Issue Date: **06/18/2018**Print Date: **06/18/2018**

	Long-term exposure can also cause a variety of respiratory symptoms. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.				
CARBON BLACK & TALC	No significant acute toxicological data identified in literature search.				
Acute Toxicity	0	Carcinogenicity	0		
Skin Irritation/Corrosion	0	Reproductivity	0		
Serious Eye Damage/Irritation	0	STOT - Single Exposure	0		
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	0		
Mutagenicity	0	Aspiration Hazard	0		

Legend:

Data available but does not fill the criteria for classification
 Data available to make classification

Data available to make classification
 Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Not Available	Not Available	Not Available	Not Available	Not Available
ENDPOINT	TEST DURATION (HR)	SPECIE	S VALUE	SOURCE
LC50	96	Fish	=1000mg/L	1
NOEC	96	Fish	=1000mg/L	1
ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Not Available	Not Available	Not Available	Not Available	Not Available
	Not Available ENDPOINT LC50 NOEC ENDPOINT	Not Available Not Available ENDPOINT TEST DURATION (HR) LC50 96 NOEC 96 ENDPOINT TEST DURATION (HR)	Not Available Not Available Not Available ENDPOINT TEST DURATION (HR) SPECIE LC50 96 Fish NOEC 96 Fish ENDPOINT TEST DURATION (HR) SPECIES	Not Available Not Available Not Available Not Available ENDPOINT TEST DURATION (HR) SPECIES VALUE LC50 96 Fish =1000mg/L NOEC 96 Fish =1000mg/L ENDPOINT TEST DURATION (HR) SPECIES VALUE

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Persistence and degradability

Ingredient Persistence: Water/Soil	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

mosmy mosm		
Ingredient	Mobility	
	No Data available for all ingredients	

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ► Containers may still present a chemical hazard/ danger when empty.
- ► Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

- ► DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Authority for disposal.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant NO

Land transport (DOT): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Version No: 1.1

Trillion Colorant SB Black - 54202

Issue Date: 06/18/2018 Print Date: 06/18/2018

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

\parallel CARBON BLACK(1333-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC
Monographs

- US Alaska Limits for Air Contaminants
- US California Permissible Exposure Limits for Chemical Contaminants
- US California Proposition 65 Carcinogens
- US Hawaii Air Contaminant Limits
- US Idaho Limits for Air Contaminants
- US Massachusetts Right To Know Listed Chemicals
- US Michigan Exposure Limits for Air Contaminants
- US Minnesota Permissible Exposure Limits (PELs)
- US New Jersey Right to Know Special Health Hazard Substance List (SHHSL): Carcinogens
- US Oregon Permissible Exposure Limits (Z-1)
- US Pennsylvania Hazardous Substance List

- US Rhode Island Hazardous Substance List
- US Tennessee Occupational Exposure Limits Limits For Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
- US Washington Permissible exposure limits of air contaminants
- US Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
- US ACGIH Threshold Limit Values (TLV)
- US ACGIH Threshold Limit Values (TLV) Carcinogens
- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Permissible Exposure Levels (PELs) Table Z1
- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory
- US TSCA Chemical Substance Inventory Interim List of Active Substances

TALC(14807-96-6) IS FOUND ON THE FOLLOWING REGULATORY LISTS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC
Monographs

- US Alaska Limits for Air Contaminants
- US California Permissible Exposure Limits for Chemical Contaminants
- US California Proposition 65 Carcinogens
- US Hawaii Air Contaminant Limits
- US Idaho Limits for Air Contaminants
- US Idaho Toxic and Hazardous Substances Mineral Dust
- US Massachusetts Right To Know Listed Chemicals
- US Michigan Exposure Limits for Air Contaminants
- US Minnesota Permissible Exposure Limits (PELs)
- US New Jersey Right to Know Special Health Hazard Substance List (SHHSL): Carcinogens
- US Oregon Permissible Exposure Limits (Z-3)
- US Pennsylvania Hazardous Substance List
- US Rhode Island Hazardous Substance List

- US Tennessee Occupational Exposure Limits Limits For Air Contaminants US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants
- US Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants
- US Washington Permissible exposure limits of air contaminants
- US Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants
- US Wyoming Toxic and Hazardous Substances Table Z-3 Mineral Dusts
- US ACGIH Threshold Limit Values (TLV)
- US ACGIH Threshold Limit Values (TLV) Carcinogens
- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Permissible Exposure Levels (PELs) Table Z1
- US OSHA Permissible Exposure Levels (PELs) Table Z3 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory
- US TSCA Chemical Substance Inventory Interim List of Active Substances

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SECTION 311/312 HAZARD CATEGORIES

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	No
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

Chemwatch: 9-552493 Page 8 of 8

Version No: 1.1

Trillion Colorant SB Black - 54202

Issue Date: **06/18/2018** Print Date: **06/18/2018**

US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)

None Reported

State Regulations

US. CALIFORNIA PROPOSITION 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm

US - CALIFORNIA PROPOSITION 65 - CARCINOGENS & REPRODUCTIVE TOXICITY (CRT): LISTED SUBSTANCE

Carbon black (airborne, unbound particles of respirable size), Talc containing asbestiform fibers Listed

National Inventory	Status
Australia - AICS	Υ
Canada - DSL	Y
Canada - NDSL	N (talc; carbon black)
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Υ
Korea - KECI	Y
New Zealand - NZIoC	Υ
Philippines - PICCS	Υ
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	06/18/2018
Initial Date	06/18/2018

CONTACT POINT

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible Concentration-Short Term Exposure Limit}$

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

^{**}PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES**