



Cabot® Solid Color Acrylic Stain + Sealer

#1800 Series

DESCRIPTION

Cabot® Solid Color Acrylic Stain + Sealer is extremely durable exterior stains for use on all wood decking, outdoor furniture and fencing, as well as cement patios and walkways. 100% acrylic finish is also water repellent and fade resistant. Solid Color Stains provide excellent adhesion to new, previously stained or painted surfaces, which are in a clean, sound condition.

PRODUCT FEATURES

- Scuff resistant
- Water repellent
- 100% Acrylic formula
- Maximum-pigmented formula to withstand heavy foot traffic

FOR USE ON

New or reconditioned wood decks, porches, outdoor furniture, steps, railings and most composite boards.

TINTING

White, Medium, Deep and Neutral Bases may be tinted with compatible universal colorants. Ready-mixed colors cannot be tinted.

COVERAGE

On smooth surfaces, approximately 400–500 sq. ft. (37–46 m²) per gallon. On rough surfaces, 200–300 sq. ft. (18–27 m²) per gallon.

Square feet can be calculated by multiplying length and width; e.g., 10' W x 25' L = 250 sq. ft. Requires a 2-coat application.

DRYING TIME

Approximately 4–6 hours depending on temperature and humidity. **Allow 24 hours before replacing furniture.**

NOTE TO USER

To ensure desired appearance and proper drying time, always finish a small test area before proceeding.

SURFACE PREPARATION

In order to be effective, a stain must be able to adhere and penetrate. Surfaces must be sound and absolutely dry. Be sure surface is free of

all dirt, mildew stains, loose wood fibers and other foreign matter. Old, loose stain should be scraped off and the edges sanded smooth for proper adhesion. New treated wood should be tested for porosity prior to application. Prepare previously stained or weathered surfaces with Cabot® Wood Cleaner to remove dirt and mildew stains, or Cabot® Wood Brightener to revive extremely weathered surfaces. Scrubbing with a stiff bristle brush is required to completely remove all dirt

and debris. Sanding may be required to completely remove all loose wood fibers. Let the surface dry 24–48 hours after cleaning to ensure dry wood. Mildew: Any mildew stains present on the surface prior to application should be removed with Cabot® Wood Cleaner. Mildew stains are not caused by the coating, nor do they represent coating failure. This product contains agents that inhibit the growth of mildew on the coating's film.

LEAD WARNING

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION

Apply with nylon or polyester brushes, stain pads or professional spray equipment. When spraying, always back-brush immediately. To ensure desired appearance and proper drying time, always finish a small test area before proceeding. Do not overapply. Shake and stir thoroughly before and during use. If project requires more than 1 container, blend all containers together to ensure uniformity. Apply to small sections at a time (1–3 boards); start at one edge of the board and work end-to-end, following through to the end of the boards to avoid lap marks. One coat application may be used on new wood; 2 coats for worn or weathered surfaces and for optimum performance.

RESTRICTIONS

Do not apply in direct sunlight, to hot surfaces or when air or surface temperature is below 50°F (10°C) or may fall below 50°F (10°C) for 48 hours after application. Do not apply over wet or damp surfaces or when rain is imminent. Do not intermix with any other products. Do not thin. Protect containers from freezing.



Cabot® Solid Color Acrylic Stain + Sealer

#1800 Series

TECHNICAL DATA

Pigment Type: Titanium dioxide, iron oxide pigments, light fast organic pigments, silica

Vehicle Type: 100% acrylic polymer system

Viscosity: 85–95 Krebs Units

Flash Point: N/A

V.O.C. Content: < 100 g/L

Solids Weight: 36%

Solids Volume: 30%

Density: 9.2 lbs./gal.

Film Thickness: 3 mil dry

*Data reported is typical of the Neutral Base and will vary by color and batch.

CLEANUP AND DISPOSAL

Clean up with warm, soapy water. Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage disposal. In case of spills, absorb with inert material such as sand or kitty litter. Dispose of empty container or unused portion in accordance with local, state and federal regulations

WARRANTY

SATISFACTION GUARANTEE LIFETIME

LIMITED WARRANTY: For complete warranty terms, visit cabotstain.com/warranty or contact customer service at 1-800-US-STAIN to request a written copy

CAUTIONS

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

PACKAGING

Bases available in quart, gallon and 5 gallon sizes, ready mix colors available in gallon.

BASE AND FILL LEVELS

	(oz./gal)
White Base (1801)	124
Neutral Base (1806)	116
Deep Base (1807)	116
Medium Base (1808)	120
Ultra White (1812)	128
New Cedar (1816)	128
Cordovan Brown (1837)	128
Driftwood Gray (1844)	128
Redwood (1880)	128

Cleveland,
OH 44115
1-800-US-STAIN
cabotstain.com
Revised:3/3/2023