



2210 Acoustical Sealant

Adhesive for polyethylene vapour barrier sheets

- Excellent adhesion
- Stays tacky, non-drying
- Flexible, non-skinning
- Water resistant

Black Jack Acoustical Sealant is a specialized adhesive for use with polyethylene vapour barriers. It also seals sound barrier partitions and walls to reduce sound transmissions. This product remains permanently tacky, and should only be used in concealed areas. Dirt and dust will collect on the exposed product, but that will not affect the product performance. This sealant can improve the Sound Transmission Class (STC) rating of a steel stud/gypsum drywall test panel from a value of 18 to a value of 49 when tested according to ASTM E 90 Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements.

PREPARATION: All surfaces must be dry and free of dust, dirt, oil, and other foreign matter.

FOR BEST RESULTS: Apply from 1° C to 35° C on interior projects. If applying in cold temperatures, store product in a heated room prior to use to ease application.

APPLICATION: For vapor barriers, apply sealant to framing and press vapor barrier material into the acoustical sealant for a firm seal. For sound deadening, use abutting the joint edge of each wall panel during installation. All joints should be filled to create a continuous acoustic barrier along the edge of each wall partition panel and outlet box.

COVERAGE RATE: Provides a 6 mm bead for a length of 29 m.

CLEAN-UP: Mineral spirits.

PRECAUTIONS: Protective clothing and eyewear should be used during application of this product. For longest life, store in controlled environment, 5° C - 30° C. Do not store in sunlight. DO NOT allow product to freeze. When transporting this product, ensure that plug is tight and tube secure and upright. Do not allow tube to tumble as this may cause plug to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle. Secure over protective cloths to prevent damage due to accidental spills. Do not use in drinking water or food systems. Do not reuse empty containers.

COMPLIANCE: Meets CGSB 19-GP-21

WARRANTY AND DISCLAIMER: GHI warrants product to be free of material defects for a period of 12 months, the "Warranty Period," from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper prep and drying conditions must be observed to achieve correct results. Should a product not perform as stated, GHI shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY GHI TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
2210-7-64	300 mL	5 cm x 5 cm x 28.5 cm	300 mL	0.55 Kg	24/case	065224221037
2210-7-84	825 mL	6.5 cm x 6.5 cm x 41.5 cm	825 mL	1.49 Kg	12/case	065224221082

© 2024 Garder-Gibson, Inc. Gardner-Gibson, Inc. P.O. Box 5449 Tampa, FL 33675 USA

Manufactured and Distributed by / Fabriqué et distribué par GHI – 2540 Rena Rd. Mississauga, Ontario L4T 3C9, Canada