

DYNA-PATCH SPACKLING & PATCHING COMPOUND

PRODUCT CODE:

2W1630 Dyna-Patch Spackling & Patching Compound

PHYSICAL PROPERTIES:

Weight Solids: 74- 78%
Density: 1.204 g/ml
WPG: 10.05
Appearance: white, smooth paste
Shelf Life: 36 months (unopened following storage recommendations)

PRODUCT DESCRIPTION AND USES:

Schwartz 2W1630 is a versatile filling compound that dries quickly to give a durable finish which resists shrinkage, cracking and sagging. It is used for filling splits, gouges, cracks, nail holes and other imperfections of dimensionally stable substrates including cured plaster, drywall, masonry and some metal.

PRODUCT ADVANTAGES:

1. Fast dry.
2. Low VOC
3. Low odour
4. Non-yellowing
5. Good sandability
6. Shrinkage, crack and sag resistant
7. Paintable

ENVIRONMENTAL INFORMATION:

VOC: max 23 g/L

APPLICATION DATA:

Suggested Uses: For interior and exterior use.
Not recommended for filling expansion joints or moving.
2W1630 is not intended to substitute epoxy-based putties or fillers intended to be used where they are recommended, nor it is recommended for surface in prolong contact with water.

Mixing Instructions: Not required
Pot Life: NA
Application Tools: Putty knife, sandpaper
Reducer: NA
Retarder: NA
Clean-up : damp rag; tools must be scraped off then wash or soak with water

DIRECTIONS FOR USE:

Surface Preparation: Remove all loose, weak or rotted material from area to be repaired. The surface must be clean, dry and free from oil and wax.

Dry Time: Drying time varies with the depth of the fill, the temperature and humidity.

Ambient Conditions: Use only when ambient conditions are 4°C to 38°C and max. 95% Humidity

Storage: Store indoor above freezing temperature up to a 35°C.

Application: Following surface preparation; Apply with a putty knife, working into cracks and holes. Apply as many coats as needed until imperfection is flush with surrounding surface. Let fully dry and sand to even out surface. Drying time varies with the depth of the fill, the temperature and humidity.

Warning: Dispose soiled rags and waste –water in accordance with local regulations. Refer to MSDS for information on safe use of this product.

LIMITATIONS and WARRANTY

The recommendations made and the information herein is based on our own and independent laboratory experience, and is believed to be accurate under controlled conditions. However, no warranty or guarantee of accuracy is made because we cannot cover every possible application of product nor anticipate every variation encountered in weather conditions, job- conditions, methods used and types of surfaces on which the product is applied. The users shall make their own tests to determine the suitability of such products for any particular purpose. Schwartz makes no warranties with respect to this product, expressed or implied, without limitation, the implied warranties of merchantability or fitness for a particular purpose.

Schwartz liability shall be limited in all events to supplying sufficient product to re-treat and/or repair the specific area to which Schwartz product has been applied. Schwartz reserves the right to have the true cause of any difficulty determined by accepted test methods. Schwartz shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

THIS WARRANTY MAY NOT BE MODIFIED OR EXTENDED BY REPRESENTATIVES OF SCHWARTZ, ITS DISTRIBUTORS OR DEALERS.