

TECHNICAL SHEET
SEMI-TRANSPARENT
LINSEED OIL STAIN
PE700841-4 • PE700841-1

DESCRIPTION

Packaging: 887 ml (PE700841-4)
 3.52 L (PE700841-1)

Passeport Élite Semi-Transparent Linseed Oil Stain protects your decks, fences and siding against the weather without detracting from the texture and graining of natural wood. Two coats are recommended for maximum protection on most new or unfinished woods. A single coat is recommended for porches, railings and outdoor furniture.

For wood substrates only.

SURFACES

- Shingles
- Shakes
- Clapboards
- Beams
- Plywood Siding
- Trim
- Decks

RECOMMENDED APPLICATORS

- Brush (natural bristle)
- Roller (medium nap)
- Airless spray (0.011 to 0.013)

TECHNICAL DATA

Colour	Clear
Type	Alkyd/Oil
Coverage	Smooth surface: 350 to 400 sq.ft./gal (9.2 to 10.5 m ² /L) Porous surface: 200 to 250 sq.ft./gal (5.3 to 6.6 m ² /L) (Spray application is 50% of above)
Drying time at 25°C (77°F)	To touch: 4 hours To stack: 12 hours To recoat: 24 hours
Exposure	Exterior

TECHNICAL SHEET
SEMI-TRANSPARENT
LINSEED OIL STAIN
PE700841-4 • PE700841-1

Specular gloss	2 at 60° ± 2
Volume solids	71.77% ± 2
Solids by weight	67.6% ± 2
Vehicule	93.74% ± 2
Pigment	6.26% ± 2
Dry film thickness	1.5 mils
Viscosity at 25°C (77°F)	45 KU ± 5
Maximum VOC	250 g/L
Flash point	39.4°C (103°F)
Thinner	Mineral spirits
Cleanup	Mineral spirits

SURFACE PREPARATION

Surface must be clean and thoroughly dry. Remove all mildew, dust, dirt, oil and grease with **Passeport Élite Deck Cleaner**. Hose down with clean water and allow to dry. Apply to rough side of clapboards for best results.

APPLICATION

Stir thoroughly. Additional light stirring during application may be necessary to maintain colour uniformity. Do not thin this product. Apply by natural bristle brushes or product can be rolled or sprayed. Avoid overlapping. Clean tools as soon as possible with mineral spirits. Stain colours vary with the type of wood. A small board of an inconspicuous section of the house should be stained first to test the stain on the actual wood. Cedar, redwood, cypress and some other woods contain a natural water soluble ingredient, "tannin", that will show as a reddish brown stain when it migrates to the wood surface. If these stains appear they may be removed by washing with a mild detergent solution and rinsing with clear water.

ARCHITECTURAL SPECIFICATIONS

- Unfinished shingles, shakes, clapboards, plywood, trim: 2 coats
- Unfinished decks, railings, fences, outdoor furniture: 1 coat
- Previously stained, semi-transparent surfaces: 1 coat

TECHNICAL SHEET
SEMI-TRANSPARENT
LINSEED OIL STAIN
PE700841-4 • PE700841-1

NOTES

1. Linseed oil semi-transparent finish can only be applied over the same colour or lighter coloured stains.
2. Semi-transparent finishes vary with different varieties of wood. Samples should be tested on the actual wood to be used, before large areas of wood are stained.
3. For maximum colour retention and mildew resistance, use an acrylic latex for topcoats.

STORAGE AND DISPOSAL

STORAGE: Store in a well-ventilated place. Keep container tightly closed. Keep cool and locked up.

DISPOSAL: Dispose of contents in accordance with applicable local, national, regional or international regulations.

RESTRICTIONS

Do NOT use over previously painted, solid stained or varnished surfaces. Temperatures of both air and surface should be at least 10°C (50°C) during application and drying time. Do not mix with any types of paint or stain. Do NOT use oil-based stains on hardboard or compressed fibre siding. All loose surface wood fibres must be completely removed.

WARNING

DANGER: Combustible Liquid. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin and eye irritation.

PRECAUTIONS: Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces- No smoking. Avoid breathing mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after using. Use only outdoors or in a well-ventilated area.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID

If exposed or concerned get medical advice.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs get medical advice.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped give artificial respiration.

IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

TECHNICAL SHEET
SEMI-TRANSPARENT
LINSEED OIL STAIN
PE700841-4 • PE700841-1

IF SWALLOWED: Immediately call a poison centre or doctor.

Contents: Mineral spirits, xylene, hydrocarbon solvent, ethylbenzene, organoclay, nonylphenol ethoxylate, methyl ethyl ketoxime.

Refer to Safety Data Sheet (SDS) for further information.

RESPONSABILITY

The user assumes full responsibility for use in accordance with instructions from the product's technical sheet. Do not alternate with another product.

IMPORTANT NOTICE

The information mentioned in this document is prepared to the best of our current knowledge and does not pretend to be complete. It is possible that an updated version of this document is available on the Passeport Élite website. In case of discrepancy, the latter takes precedence over the printed document. User is responsible to evaluate the best choice of product according to surface type and present situation before use. For more information, please contact our customer service.