



## SAFETY DATA SHEET (SDS)

Solvent-Based Sealer for Concrete | PE700603 • PE700604 • PE700605 • PE700606

Date & Version: October 11, 2022 Version 1

### Section 1. Identification

<b>Product identifier</b>	Solvent-Based Sealer for Concrete   PE700603 • PE700604 • PE700605 • PE700606
<b>Other means of identification</b>	None
<b>Recommended use and restrictions on use</b>	Resin
<b>Initial supplier identifier</b>	SCI Coatings Inc. 2821 Blvd Le Corbusier Laval, Quebec H7L 4J5 www.scicoatings.com
<b>Emergency Phone No.</b>	24-hour Emergency Telephone Number Canada (CANUTEC) 613-996-6666

### Section 2. Hazard identification

#### Classification of hazardous product (name of the category or subcategory of the hazard class)

Flammable liquid (Category 2)  
Skin irritation (Category 2)  
Eye irritation (Category 2A)  
Specific target organ toxicity – single exposure (Category 3)  
Carcinogenicity (Category 2)  
Hazardous to the aquatic environment – Chronic (Category 2)

#### Information elements (symbols, signal words, hazard statements and precautionary statements of the category/subcategory)



Danger

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H351 Suspected of causing cancer.  
H411 Toxic to aquatic life with long lasting effects.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bound container and receiving equipment.  
P241 Use explosion-proof equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 Wash hands/nails/face thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear gloves/protective clothing/eye protection/face protection.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a doctor if you feel unwell.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P302+P352 IF ON SKIN, Wash with plenty of water for several minutes.  
P333 + P313 IF SKIN irritation or rash occurs: Get medical attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P305 + P351 + P338 IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical attention.  
P308 + P313 IF exposed or concerned: Get medical attention.  
P273 Avoid release to the environment.  
P391 Collect spillage.  
P370 + P378 In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.  
P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.



## SAFETY DATA SHEET (SDS)

Solvent-Based Sealer for Concrete | PE700603 • PE700604 • PE700605 • PE700606

Date & Version: October 11, 2022 Version 1

P405 Store locked up.

P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

**Other hazards known** None

### Section 3. Composition/information on ingredients

Chemical name (common name/synonyms)	CAS number or other	Concentration (%)
t-Butyl acetate	540-88-5	15-40
4-Chlorobenzotrifluoride	98-56-6	15-40
Xylene	1330-20-7	7-13
Ethyl benzene	100-41-4	< 5
Acrylic resin	114512-63-9	10-30

\* Statement - This safety data sheet provides concentration range(s) instead of the actual concentration(s) considered trade secret(s).

### Section 4. First-aid measures

<b>Inhalation</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention if you feel unwell.
<b>Ingestion</b>	IF SWALLOWED: Immediately call a doctor. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two glasses of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration.
<b>Skin contact</b>	IF ON SKIN, Wash with plenty of water for several minutes. (15-20) SKIN irritation or rash occurs: Get medical attention.
<b>Eye contact</b>	IF IN EYES, Rinse cautiously with water for several minutes (15-20). Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Most important symptoms and effects (acute or delayed)** Causes skin irritation. Causes serious eye irritation.

**Indication of immediate medical attention/special treatment** In all cases, call a doctor. Do not forget this document.

### Section 5. Fire-fighting measures

#### Specific hazards of the hazardous product (hazardous combustion products)

Carbon oxides and other irritant/toxic gases and fumes.

#### Suitable and unsuitable extinguishing media

In case of fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish.

#### Special protective equipment and precautions for fire-fighters

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water spray may be useful in cooling equipment and cans exposed to heat and flame.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with clean-up should wear the appropriate protective equipment (See Section 8).

#### Methods and materials for containment and cleaning up

Ventilate area of release. Stop the leak if it can be done safely. Contain and absorb any spilled liquid concentrate with inert absorbent material, then place material into a container for later disposal (see Section 13). Contaminated absorbent material may pose the same hazards as the spilled product. Notify the appropriate authorities as required.

### Section 7. Handling and storage

#### Precautions for safe handling

Wear gloves/protective clothing/eye protection/face protection.

Before handling, it is very important that engineering controls are operating, and that protective equipment requirements and personal hygiene measures are being followed. People working with this chemical should be properly trained regarding its hazards and its safe use. Inspect containers for leaks before handling. Label containers appropriately. Ensure proper ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Keep away from heat, sparks and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep away from incompatible materials (Section 10). Keep containers closed when not in use. Empty containers are always dangerous. Refer also to Section 8.



## SAFETY DATA SHEET (SDS)

Solvent-Based Sealer for Concrete | PE700603 • PE700604 • PE700605 • PE700606

Date & Version: October 11, 2022 Version 1

### Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10). Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of obstruction and accessible only to trained personnel. Inspect periodically for damage or leaks.

## Section 8. Exposure controls/Personal protection

### Control parameters (biological limit values or exposure limit values and source of those values)

Exposure limits: CAS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 ppm; CAS 100-41-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA 100 ppm; CAS 540-88-5 ACGIH – TLV-TWA 200 ppm;

### Appropriate engineering controls

Use under well-ventilated conditions. Local exhaust ventilation system is recommended to maintain concentrations of contaminants below exposure limits. Make emergency eyewash stations, safety/quick-drench showers, and washing facilities available in work area.

### Individual protection measures/personal protective equipment

Respiratory protection is required if the concentrations are higher than the exposure limits. Use a NIOSH approved respirators if the exposure limits are unknown. We recommend wearing chemically protective gloves (impervious), and other protective clothing to prevent prolonged or repeated skin contact during all handling operations. We recommend wearing protective chemical splash goggles/safety glasses or other to prevent mists from entering the eyes. Wash hands/nails/face thoroughly after handling. Do not eat, drink or smoke when using this product. Practice good personal hygiene after using this material. Remove and wash contaminated work clothing before re-use.

## Section 9. Physical and chemical properties

<b>Appearance, physical state/colour</b>	Viscous liquid	<b>Vapour pressure</b>	Not available
<b>Odour</b> Characteristic		<b>Vapour density</b>	Not available
<b>Odour threshold</b> Not available		<b>Relative density</b>	0.99
<b>pH</b> Not available		<b>Solubility</b>	Not available
<b>Melting/freezing point</b> Not available		<b>Partition coefficient - n-octanol/water</b>	Not available
<b>Initial boiling point/range</b> Not available		<b>Auto-ignition temperature</b>	Not available
<b>Flash point</b> 5-23°C closed cup		<b>Decomposition temperature</b>	Not available
<b>Evaporation rate</b> Not available		<b>Viscosity</b>	Not available
<b>Flammability (solids and gases)</b> Not available		<b>VOC</b>	123 g/L
<b>Upper and lower flammability/explosive limits</b> Not available		<b>Other</b>	None known

## Section 10. Stability and reactivity

### Reactivity

Does not react under the recommended storage and handling conditions prescribed.

### Chemical stability

Stable under the recommended storage and handling conditions prescribed.

### Possibility of hazardous reactions

Accumulation of flammable/explosive vapours.

### Conditions to avoid (static discharge, shock or vibration)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take action to prevent static discharges.

### Incompatible materials

Oxidizing materials; etc.

### Hazardous decomposition products

None known

## Section 11. Toxicological information

### Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact)

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer.

### Symptoms related to the physical, chemical and toxicological characteristics

Skin irritation, redness, stinging, pain; Eye irritation, redness, tearing; Respiratory tract irritation, coughing, shortness of breath, dizziness, drowsiness, nausea and headaches.

### Delayed and immediate effects (chronic effects from short-term and long-term exposure)

Skin Sensitization – No data available;

**SAFETY DATA SHEET (SDS)**Solvent-Based Sealer for Concrete | PE700603 • PE700604 •  
PE700605 • PE700606

Date &amp; Version: October 11, 2022 Version 1

Respiratory Sensitization – No data available;  
 Germ Cell Mutagenicity – No data available;  
 Carcinogenicity – Ingredient listed by IARC, ACGIH, NTP or OSHA;  
 Reproductive Toxicity – No data available;  
 Specific Target Organ Toxicity — Single Exposure – Possible;  
 Specific Target Organ Toxicity — Repeated Exposure – No data available;  
 Aspiration Hazard – No data available;  
 Health Hazards Not Otherwise Classified – No data available.

**Numerical measures of toxicity (ATE; LD<sub>50</sub> & LC<sub>50</sub>)**

CAS 1330-8-20-7 LD<sub>50</sub> Oral - Rat - 3523 mg/kg; LC<sub>50</sub> Inhalation - Rat - 4 h – 5000 ppm; CAS 100-41-4 LD<sub>50</sub> Oral - Rat - 3500 mg/kg; LC<sub>50</sub> Inhalation - Rat - 4 h – 4000 ppm; CAS 540-88-5 LD<sub>50</sub> Oral - Rat - 4100 mg/kg; CAS 98-56-6 LD<sub>50</sub> Oral - Rat - 5546 mg/kg;  
 ATE not available in this document.

**Section 12. Ecological information**

**Ecotoxicity (aquatic and terrestrial information)** No data available for this product

**Persistence and degradability** No data available

**Bioaccumulative potential** No data available

**Mobility in soil** No data available

**Other adverse effects** Toxic to aquatic life with long lasting effects.

**Section 13. Disposal considerations****Information on safe handling for disposal/methods of disposal/contaminated packaging**

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

**Section 14. Transport information****UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations**

UN1866; RESIN SOLUTION; Class 3; PG II

**UN number; Proper shipping name; Class(es); Packing group (PG) of the 49 CFR (USA)**

UN1866; RESIN SOLUTION; Class 3; PG II

**UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)**

UN1866; RESIN SOLUTION; Class 3; PG II

**UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)**

UN1866; RESIN SOLUTION; Class 3; PG II

**Special precautions (transport/conveyance)** May also be shipped as a LIMITED QUANTITY in accordance with TDG.

**Environmental hazards (IMDG or other)** Marine Pollutant

**Bulk transport (usually more than 450 L in capacity)** Possible

**Section 15. Regulatory information****Safety/health Canadian regulations specifics**

Refer to Section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

**Environmental Canadian regulations specifics**

Refer to Section 3 for ingredient(s) of the DSL

**Safety/health/environmental outside regulations specifics**

United States OSHA information: This product is regulated according to OSHA (29 CFR).

United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.

United States TCSA information: Refer to the ingredients listed in Section 3.

National Fire Protection Association (NFPA):

HEALTH: 1 FLAMMABILITY: 3 INSTABILITY: 0 SPECIAL HAZARDS: Refer to Section 2 & 3.

HAZARD SCALE: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Proposition 65: This product does not contain a chemical known to the State of California to cause cancer or other reproductive harm.

**Section 16. Other information**



## SAFETY DATA SHEET (SDS)

Solvent-Based Sealer for Concrete I PE700603 • PE700604 •  
PE700605 • PE700606

Date & Version: October 11, 2022 Version 1

**Date of the latest revision of the safety data sheet**

February 27, 2020 Version 1 (NSS ENTREPRISE INC.)

**References** Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.

### Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute toxicity estimate
CAS	Chemical Abstract Service
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.