

TECHNICAL SHEET
ANTI-SPATTER & EASY-TO-APPLY
CEILING PAINT
PE700157 • PE700158

DESCRIPTION

A Flat latex acrylic copolymer emulsion-based coating that produces a durable and washable finish. This coating applies superbly well, avoiding spatter and minimizing lap marks. It is low-odour and cleans up easily. The lightdiffusing pigments reduce the appearance of imperfections.

USAGE

Recommended for interior new or maintenance work such as walls, ceilings.

Primed materials: gypsum, fiber wallboards, wood, plaster, concrete, concrete blocks, acoustical tiles, wallpaper.

Limitations:

- Do not use for exterior work and do not use on floors.
- Do not mix with oil products or thinners.
- Do not apply directly over steel and iron.

Advantages:

- Very low odour.
- Ready to use, easy to apply and dries rapidly.
- High hiding and non-spattering.
- Soft, smooth finish with subdued reflection finish.
- Excellent resistance to yellowing.
- Easy maintenance: washable.
- Ecological product that does not contain neither lead nor mercury and conforms to Canadian regulation on the emission of the VOCs in the architectural or industrial coatings of maintenance.

SURFACE PREPARATION

The surface to be painted has to be clean, dry and free of any grease, oil or free dust. Removal of old paint by sanding, scraping or other may generate dust or fumes that contain lead. Dull glossy surfaces by using sandpaper or an abrasive cleaner. Remove sanding dust or cleaner residue. Wear protective eyewear, waterproof gloves, and protective clothing.

STORAGE

This product shall remain stable for one year. Keep the product in a dry and cool area. Keep out the freeze. Temperature storage range is (5- 30) °C.

APPLICATION

Temperature (°C):	10 to 30 °C (50° to 86 °F)
Humidity:	Ideal: 50%. Maximum: 85%

TECHNICAL SHEET
ANTI-SPATTER & EASY-TO-APPLY
CEILING PAINT
PE700157 • PE700158

EQUIPMENT RECOMMENDATIONS (Comparable Equipment Also Suitable)

- Brush: use a nylon / polyester brush
- Roller: use a 3/8" a -3/4" nap synthetic roller cover
- Spray-Airless (filter through cheesecloth when the Airless paint sprayer is used)
 - Pressure: 2200-2400 psi
 - Tip: 0.019" – 0.021"
 - Reduction: About 10%

MAINTENANCE

To assure maximum washability and durability, allow 30 days before washing the dry paint film. When removing stains, dirt and marks, use a soft cloth or sponge with water and a solution of trisodium phosphate. Do not use abrasive cleaner or scrub to remove stains.

WASTE DISPOSAL

Reach your municipality about proper disposal procedure or give leftover paint to someone who could use it, a neighbor or friend, a recreational service or a non-profit organization. Do not pour leftover paint down the drain.

WARNING! HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION. IT MAY CAUSE ALLERGIC SKIN REACTION.

FOR INDUSTRIAL OR COMMERCIAL USE ONLY. NOT INTENDED FOR RESIDENTIAL USE. KEEP OUT OF REACH OF CHILDREN.

REFER TO PRODUCT MATERIAL SAFETY DATA SHEET (MSDS) AND LABEL WARNINGS FOR ADDITIONAL SAFETY INFORMATION.

The technical data and suggestions for use contained herein are correct to the best of our knowledge and offered in good faith. All technical information is subject to change without notice. The statements of this literature do not constitute a warranty, express or implied, as to the performance of these products. We guarantee our products to conform to Passeport Élite specifications. Due to paint application variables beyond our control, ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE, ARE HEREBY EXCLUDED. Liability, if any, is limited to replacement of the product or refund of the purchase price. Labor and other material costs are excluded from this limited warranty.

TECHNICAL SHEET
ANTI-SPATTER & EASY-TO-APPLY
CEILING PAINT
PE700157 • PE700158

TECHNICAL INFORMATIONS

Safety information

Flashpoint: Not flammable. Lead: None.

NOTE: Wear gloves & goggles. Wash skin immediately with soapy water.

Dry time

Drying time may be longer depending on humidity, temperature variation, texture and surface porosity.

Thinning

Not required.

Clean up

Water, Soap. Wait at least 30 days before any cleaning. Avoid any abrasive cleaners.

Physical properties (Calculated values are shown and may vary slightly from the actual manufactured material.)

Vehicle type	Acrylic Latex emulsion
Composition-thinner	Water
Composition-binder	Vinyl acrylic latex
Weight per gallon	11.59 ± 0.25% lb/gal.
Density	1.39 g/ml
Ph @ 100%	8 - 9
H ₂ O solubility	Complete
Odour	Mild
Clarity	Opaque
Viscosity	95 – 98 KU
Solids by weight	52.8 ± 2%
Solids by volume	34.7 ± 2%
Volatile organic compounds	< 50 g/l VOC
Coverage	280-370 ft ² /gal or 6.8 - 9.1 m ² / liter
Recommended film thickness	Wet: 4.3 – 5.8 mil Dry: 1.5 – 2.0 mil
Sheen (at 85°)	2 ± 0.5%
Tack free	1 hour
Recoat	3 - 4 hours
Packaging	3.78 L, 18.9 L