

Acrylic Series + Surface Cleaner

PE700200 • PE700201

1- Product Description

Acrylic Series + Surface Cleaner is an ultra-efficient high performance professional cleaner. It's an excellent degreaser. It can be used on almost any surface. It can revive a graying wooden structure. It's ideal for wood and concrete substrates. And clean any types of acrylic surface and any types of coatings. Avoid applying it on aluminum surfaces.

Acrylic Series + Surface Cleaner is biodegradable, with a very low toxicity level, it is non-carcinogenic and non-mutagenic. It has been developed to replace the highly toxic substances that affect the ozone layer (such as dichloromethane).

2- Coverage

Undiluted

1 L covers ± 3.7 m² (0.26 gal covers ± 40 ft²)

3.78 L covers ± 14 m² (1 gal covers ± 150 ft²)

3- Mix

Dilute with water according to the type of use.

Applications types	Product	Water
General cleaning (Stained or painted surface)	1	9
Grizzled surface	1	5
Some species of wood and plastic	1	4
Treated wood	1	0

Note: In its pure form, the product may be used for scouring a stain, but not for scouring paint.

4- Application

Apply the product early in the morning or in the shade at a temperature of 10°C to 30°C. Avoid rain. This product may blacken certain wood essence, do a test patch on a small non apparent area before application.

Before application protect vegetation and other materials that will not be treated by watering or covering with a plastic sheet. It is important to ensure that anything that can potentially be taken off is removed.

1. Wash the surface with a pressure washer. Make sure you have removed everything that can be removed.
2. Using a cloth, brush or sprayer, the product diluted as recommended by the table.
3. Let the product react for 15 minutes at a temperature above 18°C. For a more robust clean, leave on for 30 minutes to 2 hours. Keep the surface wet.
4. Rinse the surface with a pressure washer until the foam disappears (adjust the pressure to avoid damaging the coating). Rinse the surrounding surfaces.
5. Let the surface dry completely.

Acrylic Series + Surface Cleaner

PE700200 • PE700201

5- Cleaning

Notes for cleaning an acrylic surface:

Using a stiff bristle brush or hard brushing may damage the finish.

If you wash with pressure, always use a fan spray and keep the end of the jet 2 feet from the surface to be cleaned and do not exceed 600 psi, as the acrylic finish may be damaged and the guarantee voided.

Never use a solvent as a cleaner; the acrylic could be seriously damaged.

6- Personal Protection

When using the *Acrylic Series + Surface Cleaner*, it is recommended to have adequate ventilation to keep vapor concentrations in the air. Wear the following safety equipment:

- Safety goggles or protective glasses
- Chemical resistant gloves
- Long sleeves and/or rubber based protective clothing
- Boots

For indoor work: It is recommended to ensure adequate ventilation to maintain vapor concentrations in the air. If necessary:

- Wear a face mask if ventilation is inadequate. (Respirator approved / certified with organic vapor cartridges)

7- Storage

Store the *Acrylic Series + Surface Cleaner* at a controlled temperature ranging from 5 to 40°C (41 to 104°F) in a dry and sealed container. Keep away from frost. Product life cycle is of 3 years.

Packaging:

1L 12 per box

3.78L 4 per box

8- Transport conditions

Shipping Name: UN 3266

CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide)

TDG Classification: Class 8, Packing group II.

9- Physical properties

Appearance: Green liquid

Odor: soap

pH (diluted 1%): 12.5

Density: 1.1g / mL

VOC: 0%

(Volatile Organic Compounds)