

**SECTION 1. IDENTIFICATION**

<b>Product name</b>	Acrylic Series + Concrete Repair Coating - Part A
<b>Code</b>	PE700208
<b>Product description</b>	Adhesive and leveling coat.
<b>Restriction of use</b>	Sanding or grinding the dried product emits dangerous dust.
<b>Supplier</b>	Texnov inc. 839 Joseph-Louis-Mathieu Sherbrooke, Qc J1R 0X3 819-820-1188 (8h30-16h30 Monday to Friday)
<b>Emergency Phone Number</b>	<b>1-877-316-6388</b>

**SECTION 2. HAZARD IDENTIFICATION**



<b>Product classification</b>	Specific target organ toxicity - repeated exposure - Category 1
<b>Warning statements</b>	Danger
<b>Hazard statements</b>	Causes damage to organs (liver, spleen, kidneys, lymph node) after repeated exposure or prolonged exposure.
<b>Precautionary statements</b>	<p><b>Prevention:</b> Do not breathe dust / fume / gas / mist / vapors / spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when handling this product.</p> <p>Wear gloves and safety glasses. Use in a well-ventilated area. Inhalation of sanding dust or grinding of the dry product may be harmful. These dusts can cause irritation to the respiratory tract and can damage organs (lungs). This product contains ingredients that are considered carcinogenic if transformed into dust.</p> <p><b>Intervention</b> - Consult a doctor if you feel unwell.</p> <p><b>INGESTION:</b> Call Poison Control Center or doctor immediately. Do not induce vomiting unless advised by the doctor.</p> <p><b>EYES:</b> Immediately flush with plenty of water for 15 minutes, occasionally lifting the eyelids.</p> <p><b>SKIN:</b> wash with soap and water. Take off immediately all contaminated clothing.</p> <p><b>INHALATION:</b> If person is not breathing, give artificial respiration and seek medical attention. If breathing is difficult, remove victim to fresh air.</p> <p><b>STORAGE</b> - Store at 5°C to 30°C in a closed plastic container. Keep away from frost.</p> <p><b>DISPOSAL</b> - Dispose of contents and container in accordance with local regulations.</p>

**SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS**

Ingredient	CAS number	% (weight/weight)
Crystalline silica (Quartz)	14808-60-7	15-40
The crystalline silica (quartz) content of the product is considered encapsulated or embedded in the binder polymer and not bio-accessible by inhalation in normal use of the product. Based on current knowledge and applicable concentrations, there are no other ingredients in this product that are classified as hazardous by GHS and that should be reported in this section.		

**SECTION 4. FIRST AID MEASURES**

**Eye contact:** Immediately flush with plenty of water for 15 minutes, occasionally lifting the eyelids.  
 Skin contact: wash with soap and water. Take off immediately all contaminated clothing.  
**Ingestion:** Call Poison Control Center or doctor immediately. Do not induce vomiting unless advised by the doctor.  
**Inhalation:** If person is not breathing, give artificial respiration and seek medical attention. If breathing is difficult, remove victim to fresh air.

**SECTION 5. FIRE-FIGHTING MEASURES**

**Non-flammable product**, but it may splash if heated above boiling point.  
**Combustion product:** If the product is heated to combustion, after the release of water vapor, carbon oxides will be emitted.  
**Use the appropriate extinguishers.**

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Pick up all the scattering with a shovel and eliminate the discards. Do not send the dispersions into the sewers, occurs can clog the piping.

**SECTION 7. HANDLING AND STORAGE**

**Handling safety precaution:** Do not eat, smoke or drink in the work area. Wash hands after handling. Avoid contact with hands and eyes.  
**Storage safety conditions:** Keep in a dry place away from frost and sunlight. The product may coagulate. The storage temperature is 5°C to 30°C. Keep in a closed plastic container.

**SECTION 8. EXPOSURE CONTROL / PERSONAL PROTECTION**

**CONTROL PARAMETERS:**  
**Occupational Exposure Limits:** Sanding or grinding this product in its dry form may produce particles of crystalline silica.

Breathable dust	RSST		ACGIH TLV		
	Ingrédient	VEMP	DIVS	TWA	STEL
Crystalline silica (Quartz)	0.1 mg/m <sup>3</sup>	50 mg/m <sup>3</sup>	0.025mg/m <sup>3</sup>	Not available	

RSST : Regulation respecting occupational health and safety.  
 VEMP : Weighted average exposure value.  
 DIVS : Immediate danger to life and health.  
 ACGIH : American Conference of Governmental Industrial Hygienists,  
 TLV : Threshold limit value.  
 TWA : Time-weighted average.  
 STEL : Short-term exposure limit

**Individual protection measures**  
**Respiratory protection:** Wear appropriate respiratory protection if dusts / fumes / gases / mists / vapors / aerosols are possible above permissible limits. Use in a well ventilated place.  
**Eye Protection:** To reduce exposure, wear safety glasses.  
**Hand protection:** To reduce exposure, wear gloves. Wash your hands thoroughly after using the product. Do not eat, drink or smoke when handling this product.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance</b>	Creamy with a slight pink color.
<b>Odor</b>	Low odor of ammonia
<b>Odor threshold</b>	Not available
<b>pH</b>	9-9,5.
<b>Freezing point</b>	0°C
<b>Boiling point</b>	100°C
<b>Evaporation rate</b>	Not available
<b>Flammability (solid and gas)</b>	Not applicable
<b>Explosive limit</b>	Not applicable
<b>Vapor pressure</b>	Not available
<b>Vapor density</b>	Not available
<b>Relative density</b>	1,5
<b>Solubility in water</b>	May be diluted with water.
<b>Partition coefficient n-octanol / water</b>	Not available
<b>Auto-ignition temperature</b>	Not applicable
<b>Decomposition temperature</b>	Not available
<b>Viscosity</b>	12000 mm <sup>2</sup> / s (converted from measurement on Brookfield).

**SECTION 10. STABILITY AND REACTIVITY**

**Chemical stability:** This product is considered stable under recommended storage conditions.  
**Reactivity:** Incompatible with strong oxidants and strong acids.  
**Possibility of hazardous reactions:** This product can not polymerize.  
**Hazardous decomposition product:** If the product is heated to combustion, there will be emission of carbon oxides.

**SECTION 11. TOXICOLOGICAL INFORMATION**

<b>Routes of entry</b>	This product may be absorbed through the respiratory, digestive and cutaneous routes.		
<b>Acute toxicity (calculated GHS):</b>			
Produit	DL <sub>50</sub> oral, mg/kg	DL <sub>50</sub> cutaneous, mg/kg	CL <sub>50</sub> , mg/L
Concrete Repair Coating	> 10000 (rat)	> 10000 (lapin)	> 100 (rat)
<b>Skin irritation</b>	Virtually nil. An irritation of a mechanical nature is possible.		
<b>Eye irritation</b>	Not important. An irritation of a mechanical nature is possible.		
<b>Respiratory or skin sensitization</b>	Virtually nil.		
<b>Specific target organ toxicity</b>	Causes damage to organs (liver, spleen, kidneys, and lymph node) after repeated exposure or prolonged exposure. Extract from the toxicological index linked to this mention: A very small proportion of silica can pass into the bloodstream in the form of silicic acid. The latter can be deposited in the liver, spleen and lymph nodes. The silicic acid is then excreted unchanged via the kidneys		
<b>Carcinogenicity</b>	The sanding or grinding of this product in its dry form can produce particles of crystalline silica which are considered carcinogens classified 1 according to IARC. Repeated inhalation of crystalline silica can cause lung damage and silicosis.		
<b>Ingredient</b>	CIRC	ACGIH	NTP
Crystalline silica (Quartz)	Group 1	Group A2	K
CIRC : International Center for Research on Cancer. Group 2B : May be carcinogenic to humans. Group A4 : Nonclassifiable substance as a carcinogen to humans. NTP : National Toxicology Program. N : Negative.			
<b>Reproductive toxicity</b>	None		
<b>Germ cell mutagenicity</b>	None		

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicology:** Not available  
**Bioaccumulative potential:** Not available.  
**Volatile organic compounds (V.O.C.) :** ≤ 50g / L.



**SAFETY DATA SHEET (SDS)**  
Passeport Elite Acrylic Series +  
Concrete Repair Coating 26 kg - Part A  
PE700208

**SECTION 13. DISPOSAL CONSIDERATIONS**

Dispose of According to Municipal, Provincial and National Regulations.

**SECTION 14. TRANSPORT INFORMATION**

Shipping Name.....Not Applicable.  
TDG Classification .....Not Regulated.

**SECTION 15. REGULATORY INFORMATION**

WHMIS 2015 Classification: Specific target organ toxicity, repeated exposure, Category 1.  
The product classification and the SDS have been developed in accordance with the HPR.

**SECTION 16. OTHER INFORMATION**

**SDS prepared by:** Texnov inc.  
**Emergency telephone number:** 1-877-316-6388  
**Revision Date:** 2024-07-07  
**Warning:** The information and recommendations contained in this document have been written to the best of knowledge and technical data collected by Texnov Inc. at the time of the revision. This document is intended to inform users of the product about the precautionary measures when using the product. No warranty is given on the properties mentioned on the products. No liability will be assumed for cases of misuse of the product or failure to observe the safety instructions contained in this document.