


SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. A (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

SECTION 1. IDENTIFICATION	
Product identifier	Industrial Epoxy-Based Crack Filler - Comp. A (4h and 8h)
Other Means of Identification	PE700229 • PE700230
Recommended Use	Epoxy Resin, Crack filler fast cure
Restrictions on Use	Unknown
Supplier Identifier	SCI COATINGS INC. 2821 Boul. Le Corbusier Laval, Quebec Canada H7L 4J5 Web: www.sealchem.com
Emergency Phone No.	24-Hour Emergency Telephone Number Canada (CANUTEC): (613) 996-6666

SECTION 2. HAZARD IDENTIFICATION	
Classification	Skin Sensitization Category 1B Skin Corrosion/irritation Category 2 Serious eye damage/irritation Category 2A Acute Toxicity, Oral Category 5 Hazardous to the aquatic environment - acute Category 2 Hazardous to the aquatic environment - chronic Category 2
Label Elements	
	
Signal Word	Warning
Hazard Statements	H303: May be harmful if swallowed H315: Causes skin irritation H317: May cause an allergic skin reaction H319: Causes serious eye irritation H401: Toxic to aquatic life H411: Toxic to aquatic life with long lasting effects
Precautionary statements	Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash with plenty of water and soap thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/eye protection. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/attention. P302 + P352 IF ON SKIN: Wash with plenty

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. A (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

of water. P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P312 IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell. P362 + P364 Take off contaminated clothing and wash before reuse. P273 Avoid release to the environment. P391 Collect spillage. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

Chemical Name	CAS No.	% concentration
Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin	25085-99-8	60 - 100 %
4-Nonyl phenol branched	84852-15-3	1 - 10 %

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Ingestion:

IF SWALLOWED: Call a POISON Center/doctor/...if you feel unwell.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eye damage.

If Ingested:

Ingestion is likely to be harmful or have adverse effects

Immediate Medical Attention and Special Treatment:

Special Instructions:

If a physician or medical attention is required, have product container or label at hand.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO2)

Unsuitable Extinguishing Media

water jet

Specific Hazards Arising from the Product

During fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating.

Special Protective Equipment and Precautions for Fire-fighters

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. A (4h and 8h)
PE700229 • PE700230

Date et version : November 10, 2022, Version 1

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire-fighting clothing. Avoid contact with this material during fire-fighting operations. If contact is likely, change to full chemical resistant fire-fighting clothing with self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Isolate area. Keep unnecessary and unprotected personnel away. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillage cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Clean up

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid use of electric band heaters. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incompatible materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under <http://www.ccohs.ca/topics/hazards/chemical/chemicals/>

Appropriate Engineering Controls

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. A (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures



General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Paste, Creamy white color
Odor	Not available
Odor threshold	Not available
pH	Not available
Melting Point	Not available
Initial Boiling Point / Range	Not Available
Flash point	>93
Evaporation rate	Not available
Flammability (solid; gas)	Not available
Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	1.21
Solubility	Partial
Partition coefficient – n- Octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. A (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

SECTION 10. STABILITY AND REACTIVITY	
Reactivity	Non-reactive
Chemical stability	Stable under recommended handling and storage conditions
Possibility of Hazardous reactions	This product will polymerize if mixed with an amine. Considerable heat can evolve.
Conditions to avoid	Avoid temperatures exceeding the flash point. Avoid unintended contact with amines.
Incompatible materials	Strong oxidizers, strong alkalis, strong mineral acids, amines.
Hazardous decomposition products	Unknown

SECTION 11. TOXICOLOGY INFORMATION
<p>Likely Routes of Administration Inhalation, skin contact, eye contact, ingestion.</p> <p>Acute Toxicity Oral: Harmful if swallowed. Dermal: Harmful in contact with skin.</p> <p>LD50 and LC50 Data Not available</p> <p>Skin Corrosion/Irritation Causes skin irritation.</p> <p>Serious Eye Damage/ Irritation Causes serious eye damage</p> <p>STOT (Specific Target Organ Toxicity) – Single Exposure Inhalation No data</p> <p>Aspiration Hazard Not classified based on available data.</p> <p>STOT(Specific Target Organ Toxicity) – Repeated Exposure No data</p> <p>Respiratory and/or Skin Sensitization May irritate mucous membranes, eyes, nose, and respiratory passages. May cause asthma attack to persons with pre-existing bronchial hyper reactivity. Exposure to high concentrations may lead to bronchitis, bronchial spasm and pulmonary oedema. Effects are usually reversible. May cause C.N.S. depression with symptoms of nausea, light-headedness, drowsiness, dizziness, loss of coordination</p> <p>Carcinogenicity Unknown</p> <p>Reproductive Toxicity Not available</p> <p>Germ Cell Mutagenicity Not available</p>

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. A (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

Interactive Effects

Not available

SECTION 12. ECOLOGICAL INFORMATION

Hazardous to aquatic environment

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

SECTION 14. TRANSPORT INFORMATION

UN Number: Proper shipping name: Class(es): Packing group (PG) of the TDG Regulations:

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

UN Number: Proper shipping name: Class(es): Packing group (PG) of the IMDG (maritime):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

UN Number: Proper shipping name: Class(es): Packing group (PG) of the IATA (air):

UN3082; ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bisphenol-A-(epichlorhydrin) epoxy resin); CLASS 9; PG III

SECTION 15. REGULATORY INFORMATION

Safety/health Canadian regulations specifics: Refer to section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

SECTION 16. OTHER INFORMATION

Date of Preparation	August 2020
Date of Last Revision	June 1, 2014
Revision Indicators	The entire MSDS was change in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.
References	1. CHOHS Fact Sheets September 2016 ©CCOHS 2016 2. Supplier's Material Safety Data Sheet(s)
ACGIH ATE CAS	American Conference of Governmental Industrial Hygienists Acute toxicity estimate Chemical Abstract Service

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. A (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System


Notice: The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that SCI Coatings Inc will not be liable for any damages resulting from its use since SCI Coatings Inc cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

SECTION 1. IDENTIFICATION	
Product identifier	Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
Other Means of Identification	PE700229 • PE700230
Recommended Use	Epoxy Hardener Crack Filler
Restrictions on Use	Unknown
Supplier Identifier	SCI COATINGS INC. 2821 Boul. Le Corbusier Laval, Quebec Canada H7L 4J5 Web: www.sealchem.com
Emergency Phone No.	24-Hour Emergency Telephone Number Canada (CANUTEC): (613) 996-6666

SECTION 2. HAZARD IDENTIFICATION	
Classification	Flammable Liquids (Category 4) Acute Toxicity, Oral (Category 4) Acute Toxicity, Dermal (Category 4) Skin Sensitization (Category 1) Respiratory Sensitization (Category 1) Skin Corrosion/irritation (Category 1B) Serious eye damage/irritation (Category 1) Reproductive toxicity, Additional category lactation Reproductive toxicity, fertility (Category 2) Reproductive toxicity, unborn child (Category 1B) Specific target organ toxicity - single exposure (Category 3 irritating to respiratory system) Hazardous to the aquatic environment - acute (Category 1) Hazardous to the aquatic environment - chronic (Category 1)
Label Elements	
Signal Word	Danger
Hazard Statements	H227 Combustible liquid H302 Harmful if swallowed H312 Harmful in contact with skin H317 May cause an allergic skin reaction H314 Causes severe skin burns and eye damage H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

- H335 May cause respiratory irritation
- H360 May cause harm to breast-fed children
- H361 May damage the unborn child. Suspected of damaging fertility
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

Precautionary statements

Prevention:

P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P260 Do not breathe dust or mist. P263 Avoid contact during pregnancy/while nursing. P264 Wash with plenty of water and soap thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P284 Wear respiratory protection. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. P310 Immediately call a POISON CENTER or doctor/physician. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P341 + P311 IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P362 + P364 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use water spray, dry powder, or foam for extinction. P233 Keep container tightly closed. P405 Store locked up. P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

GHS SPECIAL LABELING: **EUH205** - "Contains epoxy constituents. May produce a skin allergy."

SECTION 3. COMPOSITION

Chemical Name	CAS No.	% concentration
epoxy adduct	Proprietary	1 - 10 %
isophorone diamine	2855-13-2	10 - 20 %
benzyl alcohol	100-51-6	1 - 10 %
4-nonylphenol, branched	84852-15-3	10 - 20 %
polyoxypropylene diamine	9046-10-0	15 - 25 %
amine curing agent	Mixture	35 - 55 %

SECTION 4. FIRST-AID MEASURES

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
PE700229 • PE700230

Date et version : November 10, 2022, Version 1

First-aid Measures

Inhalation:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact:

Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.

Ingestion:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most Important Symptoms and Effects, Acute and Delayed

If inhaled:

Burning pain and severe corrosive skin damage. Can burn mouth, throat, and stomach. Can cause severe irritation and burns to the respiratory tract. May cause an allergic respiratory reaction. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

If on skin:

Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction

If in eyes:

Causes serious eye damage.

If Ingested:

Ingestion is likely to be harmful or have adverse effects

Immediate Medical Attention and Special Treatment:

Special Instructions:

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO₂)

Unsuitable Extinguishing Media

Water jet

Specific Hazards Arising from the Product

During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed.

Special Protective Equipment and Precautions for Fire-fighters

Self-contained breathing apparatus and turn-out gear must be worn in case of fire.

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
PE700229 • PE700230

Date et version : November 10, 2022, Version 1

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep upwind. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillage cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Clean up

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust or mist. Do not get in eyes, on skin, or on clothing. Do not get this material in contact with eyes. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Keep away from sources of ignition -No smoking. Take precautionary measures against static discharge.

Conditions for Safe Storage

Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incompatible materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation.

Data not available. For additional information, please consult the corresponding requirements under <http://www.ccohs.ca/topics/hazards/chemical/chemicals/>

Appropriate Engineering Controls

Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures



General Measures

Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection

Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection

Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection

If insufficient ventilation, wear respiratory protection.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Paste, Creamy yellow
Odor	Not available
Odor threshold	Not available
pH	Not available
Melting Point	Not available
Initial Boiling Point / Range	Not available
Flash point	>53 C
Evaporation rate	Not available
Flammability(solid; gas)	Not available
Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	1.12
Solubility	Partial
Partition coefficient – n- Octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	Non-reactive
-------------------	--------------

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

Chemical stability	Stable under recommended handling and storage conditions
Possibility of Hazardous reactions	This product will polymerize if mixed with an epoxy resin. Considerable heat can evolve.
Conditions to avoid	Avoid temperatures exceeding the flash point. Epoxy resins under uncontrolled conditions.
Incompatible materials	Strong oxidizing agents and acids.
Hazardous decomposition products	Unknown

SECTION 11. TOXICOLOGY INFORMATION

Likely Routes of Administration

Inhalation, skin contact, eye contact, ingestion.

Acute Toxicity

Oral: Harmful if swallowed.

Dermal: Harmful in contact with skin.

LD50 and LC50 Data

Not available

Skin Corrosion/Irritation

Causes skin irritation.

Serious Eye Damage/ Irritation

Causes serious eye damage

STOT (Specific Target Organ Toxicity) – Single Exposure Inhalation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Aspiration Hazard

Not classified based on available data.

STOT (Specific Target Organ Toxicity) – Repeated Exposure

Skin, eyes, central nervous system, respiratory system

Respiratory and/or Skin Sensitization

No data

Carcinogenicity

Unknown

Reproductive Toxicity

Not available

Germ Cell Mutagenicity

Not available

Interactive Effects

Not available

SECTION 12. ECOLOGICAL INFORMATION

Toxic to aquatic life with lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
 PE700229 • PE700230

Date et version : November 10, 2022, Version 1

Disposal Methods

Dispose of contents/container into safe container in accordance with local, regional or national regulations.

SECTION 14. TRANSPORT INFORMATION

UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:
 UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG II

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):
 UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG II

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):
 UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG II

SECTION 15. REGULATORY INFORMATION

Safety/health Canadian regulations specifics: Refer to section 2 for the appropriate classification. This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

SECTION 16. OTHER INFORMATION

Date of Preparation	August 2020
Date of Last Revision	June 1, 2014
Revision Indicators	The entire MSDS was change in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.
References	1. CHOHS Fact Sheets September 2016 ©CCOHS 2016 2. Supplier's Material Safety Data Sheet(s)
ACGIH ATE CAS DSL IARC IATA IMDG LC LD NIOSH NTP OSHA PEL STEL TDG	American Conference of Governmental Industrial Hygienists Acute toxicity estimate Chemical Abstract Service Domestic Substance List International Agency for Research on Cancer International Air Transport Association International Maritime Dangerous Goods Code Lethal concentration Lethal Dosage National Institute for Occupational Safety and Health National Toxicology Program (U.S.A.) Occupational Safety and Health Administration (U.S.A.) Permissible Exposure Limit Short-term Exposure Limit Transport of dangerous goods in Canada



SAFETY DATA SHEET (SDS)

Industrial Epoxy-Based Crack Filler - Comp. B (4h and 8h)
PE700229 • PE700230

Date et version : November 10, 2022, Version 1

TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

Notice: The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that SCI Coatings will not be liable for any damages resulting from its use since SCI Coatings Inc cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.