



Distributions Fillion Marquis International Itée

925 Rue Gaudette, Saint-Jean-sur-Richelieu (Québec) J3B 7S7
Tel : 450 349-2226 • Fax : 450 349-1799 • Toll Free : 1 877 989-2226
passeportelite.com

TECHNICAL DATA SHEET

STEINA INTERIOR
PENETRATING OIL
PE700654 to PE700658
PE700661 to PE700665

DESCRIPTION

STEINA Interior Penetrating Oil is formulated with a unique base to allow deep penetration and provide a rich color. It is ideal for all interior wood surfaces: furniture, cabinets, doors, woodwork, and floors.

Size 472ml

Tintable base (414ml) - PE700654
Obsidian - 1000 - PE700655
Rose Quartz - 1001 - PE700656
Aged Bark - 1002 - PE700657
Sunlit Dune - 1003 - PE700658

Size 946ml

Tintable base (850ml) - PE700661
Obsidian - 1000 - PE700662
Rose Quartz - 1001 - PE700663
Aged Bark - 1002 - PE700664
Sunlit Dune - 1003 - PE700665

PRIMARY APPLICATION

- Furniture
- Woodwork
- Cabinets
- Floors
- Doors

TECHNICAL DATA

Resin Type	Alkyd, oil
Pigments	Organic and inorganic
Solvent	De-aromatized hydrocarbon solvent (low odor)
Flash point	68.5°C (closed cup)
VOC	< 250 g/L
Solids	74–81% (by weight); 75–78% (by volume)
Density	0.93–1.18 g/ml
Viscosity	35–40 seconds, Zahn Cup #2 at 25°C
Dry Time	6–8 hours at 25°C and 50% relative humidity
Coverage	160-210 sq.ft / liter depending on wood porosity and texture
Storage	Store in a cool, dry place. KEEP OUT OF REACH OF CHILDREN.
Shelf Life	Minimum 1 year in a tightly sealed container.

SURFACE PREPARATION

Bare Wood

Surfaces must be clean, dry, and free from dirt, wax, grease, glue, and other contaminants. Sand surfaces evenly with 120 or 150 grit sandpaper and thoroughly remove dust.

Previously Finished Wood

Remove all existing finish using sandpaper or a stripper. If using a stripper, follow the manufacturer's instructions carefully.

TDS

PE700654 to PE700658
PE700661 to PE700665
April 2026



Distributions Fillion Marquis International Itée

925 Rue Gaudette, Saint-Jean-sur-Richelieu (Québec) J3B 7S7
Tel : 450 349-2226 • Fax : 450 349-1799 • Toll Free : 1 877 989-2226
passeportelite.com

TECHNICAL DATA SHEET

**STEINA INTERIOR
PENETRATING OIL**
PE700654 to PE700658
PE700661 to PE700665

COLOR TESTING

It is recommended to test the product beforehand in an inconspicuous area to determine if the desired color and effect are achieved. The final color will be affected by the wood species' natural color, which may vary.

***Base that can be tinted with up to 12 fluid ounces per gallon of compatible universal colorants.

APPLICATION

Step 1

Mix well before and during application.

Step 2

Apply the stain evenly to the surface using a brush or soft cloth, wait 5–10 minutes, then wipe off the excess with a clean, soft cotton pad.

Step 3

Allow the stain to dry for at least 8 hours before applying an oil-based varnish or any Saman water-based varnish.

Use of Penetrating Oil

STEINA Interior Penetrating Oil gives wood a rich hue and, once completely dry, can be coated with varnish. It can also be used as a standalone finish, offering a rustic natural look similar to interior wood oils. It can be buffed to achieve a satin finish. Do not clean oiled surfaces for 28 days. Use a cleaner designed for oiled surfaces.

CLEAN UP

Clean tools with mineral spirits (paint thinner)

IMPORTANT NOTICE

To the best of our knowledge, the information contained herein is accurate. Since conditions and methods are beyond our control, no warranty is expressed or implied as for the final result. The user is advised to access the suitability of the product on a test area before application.