



Distributions Fillion Marquis International Itée

925 Rue Gaudette, Saint-Jean-sur-Richelieu (Québec) J3B 7S7
Tel : 450 349-2226 • Fax : 450 349-1799 • Toll Free : 1 877 989-2226
passeportelite.com

TECHNICAL DATA SHEET
STEINA PERFORMANCE 3 IN 1
PE700668 to PE700672
PE700675 to PE700679

DESCRIPTION

STEINA Performance 3 in 1 is a water-based hybrid stain recommended for interior wood surfaces: furniture, woodworks, doors, cabinets, etc. The unique formulation based on a hybrid resin dispersion seals, stains and varnishes in one step. It will reveal the beauty of natural wood grain and provide a protective finish, with the added benefits of low odor and fast drying time.

Size 472ml

Tintable base (414ml) - PE700668
Ancien Gold - 800 - PE700669
Onyx - 801 - PE700670
Royal Mahogany - 802 - PE700671
Rosewood - 803 - PE700672

Size 946ml

Tintable base (850ml) - PE700675
Ancien Gold - 800 - PE700676
Onyx - 801 - PE700677
Royal Mahogany - 802 - PE700678
Rosewood - 803 - PE700679

PRIMARY APPLICATION

- Furniture
- Woodwork
- Cabinets
- Doors

TECHNICAL DATA

pH	7.7-8.1
Solids	26 ± 2 % (by weight); 23 ± 2 % (by volume)
Viscosity	45-50 seconds (Ford cup #4) at 77 °F
Density	1.02-1.05 kg/l
Drying Time	Approximately 2-4 hours at 70°F and 50% relative humidity
Coverage	Up to 160-210 sq. ft/L
VOC	< 250g/L
Gloss Levels	mat (one coat), satin (two coats), semi-gloss (three coats)
Recommended applicator	Natural bristle brush, foam brush or roll
Storage	Minimum temperature 41°F, maximum temperature 95°F. SENSITIVE TO FREEZING: CAN WITHSTAND A SINGLE FREEZE CYCLE BUT IS SENSITIVE TO PROLONGED FREEZING. KEEP OUT OF REACH OF CHILDREN.
Shelf Life	At least 1 year in a well closed container

SURFACE PREPARATION

First, surfaces must be clean, dry and free of wax, grease, dirt and dust. Then, wood surfaces should be sanded smoothly. **Do not use steel wool.** Once surface preparation is complete, mix the stain thoroughly before use.



Distributions Fillion Marquis International Itée

925 Rue Gaudette, Saint-Jean-sur-Richelieu (Québec) J3B 7S7
Tel : 450 349-2226 • Fax : 450 349-1799 • Toll Free : 1 877 989-2226
passeportelite.com

TECHNICAL DATA SHEET

STEINA PERFORMANCE 3 IN 1

PE700668 to PE700672

PE700675 to PE700679

APPLICATION

Step 1

Mix well before and during application.

Step 2

For best results, apply uniformly 2 coats in the direction of wood grain using a clean natural bristle brush. Take off the excess with a clean brush. Work on small sections at a time to prevent lap marks. Let dry and sand lightly between coats.

For extra protection, it is possible to recoat with one of the STEINA varnishes.

Step 3

Let dry completely surfaces and wait at least 21 days before cleaning. Cures in 21 days.

CLEAN UP

Clean applicator and equipment with soapy water immediately after use

IMPORTANT NOTICE

To the best of our knowledge, the information contained herein is accurate. Since conditions and methods are beyond our control, no warranty is expressed or implied as for the final result. The user is advised to access the suitability of the product on a test area before application.