

Distributions Fillion Marquis International Itée

420 Industriel Blvd., local 100, Saint-Jean-sur-Richelieu, QC J3B 4S6 Tel.: 450-349-2226 • Fax: 450-349-1799 • Toll free: 1-877-989-2226

# passeportelite.com

# TECHNICAL SHEET STEINA END CUT SEALER PE700881 • PE700882

## **DESCRIPTION**

Packaging: 946 ml

**STEINA End Cut Sealer** weatherproofs cut ends exposing untreated wood. It prevents checking and warping and protects wood from rotting. This ready-to-use water-based product is ideal for exterior softwood, hardwood and exotic wood above-ground surfaces.

PE700881 Natural - 610 PE700882 Brown - 680

- Water-based, non-toxic formula
- Pressure treated wood preservation
- Ready to use
- Easy to apply
- Good wood surface penetration
- For all types of hardwood and softwood
- Moisture repellent
- Anti-splitting
- Very low VOC content

#### **TECHNICAL DATA**

рН	7.8-8.2
Solids	33 ± 1% (by weight)
Viscosity	38-40 seconds Ford cup #4
Density	0.97-0.98 kg/L
Drying time	Approximately 1 hour at 20°C (68°F) and 50% relative humidity
Coverage	Approximately 250 sq. ft. per gallon (23 sq. m. per 3.78 L) Coverage will vary depending on surface porosity and preparation.
VOC	3 g/L
Applicators	Bristle brush, 10 mm lint-free roller or spray gun.
Clean up	Warm soapy water
Storage	Minimum temperature 5°C (41°F) Maximum temperature 35°C (95°F) PROTECT FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.
Shelf life	At least 1 year in a well closed container



**Distributions Fillion Marquis International Itée**420 Industriel Blvd., local 100, Saint-Jean-sur-Richelieu, QC J3B 4S6
Tel.: 450-349-2226 • Fax: 450-349-1799 • Toll free: 1-877-989-2226

passeportelite.com

TECHNICAL SHEET STEINA END CUT SEALER PE700881 • PE700882

## **APPLICATION CONDITIONS**

Air and surface temperature should be between 12°C and 25°C (53°F and 77°F). Relative humidity should be between 15 and 50%. Do not apply if rain is expected within 12 hours.

#### SURFACE PREPARATION

The product can be applied on a damp surface but not wet.

#### **APPLICATION**

Stir thoroughly. Test the product in a small, inconspicuous area. Apply generously in a single coat with a quality bristle brush, a 10 mm lint-free roller or a spray gun. Clean all equipment with hot soapy water immediately after use.

# LIMITATION OF WARRANTY

The manufacturer's liability, expressed or implied, is limited to the replacement of the product. The user assumes full responsibility for use in accordance with the product data sheet. The manufacturer is not liable for any direct, indirect, consequential, economic or other damages.

