


SECTION 1. IDENTIFICATION

Product identifier	Light Grey #885 Passeport Elite Floor Epoxy - Part B PE700911
Other Means of Identification	N.A.
Recommended Use	Epoxy coating
Recommended on Use	Unknown
Supplier Identifier	SCI COATINGS INC. 8320 Rue Grenache, Anjou, Québec Canada H1J 1C5 www.scicoatings.com
Emergency Phone No.	24-Hour Emergency Telephone Number Canada (CANUTEC): (613) 996-6666

SECTION 2. HAZARD IDENTIFICATION

Classification	
Acute Toxicity, Oral Category 4 Skin Sensitization Category 1A Skin Corrosion/irritation Category 1B Serious eye damage/irritation Category 1 Reproductive toxicity Category 2 Hazardous to the aquatic environment - acute Category 1 Hazardous to the aquatic environment - chronic Category 1	
Label Elements	
	
Signal Word	
Danger	
Hazard Statements	
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H361	May damage the unborn child. Suspected of damaging fertility
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects



Safety Data Sheet (SDS)
Light Grey #885 Passeport Elite Floor Epoxy - Part B
PE700911

Precautionary statements

Prevention:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust or mist.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P270 Do not eat, drink or smoke when using this product.
- P264 Wash with plenty of water and soap thoroughly after handling.
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
- P310 Immediately call a POISON CENTER or doctor/physician.
- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [shower].
- P310 Immediately call a POISON CENTER or doctor/physician. P363 Wash contaminated clothing before reuse.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P312 Call a POISON CENTER/doctor if you feel unwell.
- P362 + P364 Take off contaminated clothing and wash before reuse.
- P273 Avoid release to the environment.
- P405 Store locked up.
- P501 Dispose of contents/container into safe container in accordance with local, regional or national regulations.

Other Hazards: Unknown

SECTION 3. COMPOSITION

Chemical Name	CAS No.	% concentration
Isophorone diamine	2855-13-2	20 - 25%
Benzyl alcohol	100-51-6	5 - 10%
4-nonylphenol, branched	84852-15-3	25 - 30%
Proprietary component 1	Proprietary	15 - 25 %



SECTION 4. FIRST-AID MEASURES

First-aid Measures
Inhalation:
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Skin Contact:
Flush with soap and water for a minimum of 15 minutes. Consult a physician if irritation persists or you feel unwell.
Eye Contact:
Rinse immediately with plenty of water for at least 15 minutes. Consult a physician.
Ingestion:
Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

Most Important Symptoms and Effects, Acute and Delayed If inhaled:
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
If on skin:
Harmful if in contact with the skin. Causes skin irritation. Exposure may produce an allergic reaction.
If in eyes:
Causes serious eye damage.
If Ingested:
Ingestion is likely to be harmful or have adverse effects.

Immediate Medical Attention and Special Treatment:
Special Instructions:
If a physician or medical attention is required, have product container or label at hand.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media
Suitable Extinguishing Media
In case of fire: water fog, foam, dry chemical powder, carbon dioxide (CO²)
Unsuitable Extinguishing Media
Water jet

Specific Hazards Arising from the Product
During fire, nitrous gases, fumes/smoke, isocyanates and vapour may be formed.

Special Protective Equipment and Precautions for Fire-fighters
Self-contained breathing apparatus and turn-out gear must be worn in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures
Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

Methods and Materials for Containment and Clean up
For containment, ensure adequate ventilation and absorb any spill with inert liquid binding material and dispose of waste safely.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling
 Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapors of the product should be ventilated and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to wellventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

Conditions for Safe Storage
 Store in cool dry and well-ventilated place. Keep stored in accordance with local, regional, national, and international regulations. Store away from incompatible materials.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters
 All protective clothing should be appropriately clean and available to dress into before work. The engineering measures or controls and PPE recommendations are only guidelines and may not apply to every situation. Data not available. For additional information, please consult the corresponding requirements under <http://www.ccohs.ca/topics/hazards/chemical/chemicals/>

Chemical Name	ACGIH® TLV®		OSHA PEL	AIHA®	WEEL®
	TWA	STEL®	TWA Ceiling	8-hr TWA	Short-Term

Appropriate Engineering Controls
 Local exhaust ventilation required. Make up air should be supplied to balance air that is removed by local or general exhaust ventilation. Provide sufficient ventilation to keep vapors below permissible exposure limit. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national / local regulations are observed.

Individual Protection Measures



General Measures
 Do not eat, drink or smoke during work. Avoid all contact with skin or eye. If clothing comes into contact with material, do not allow out of the workplace. Clean hands and any exposed skin thoroughly after work and before breaks.

Eye / Face Protection
 Use tightly sealed goggles or safety glasses with side shields which are resistant to Chemicals.

Skin Protection
 Wear chemical resistant protection gloves. Wear impervious clothing as necessary to protect against coming in contact with product.

Respiratory Protection
 If insufficient ventilation, wear respiratory protection.



Safety Data Sheet (SDS)

Light Grey #885 Passeport Elite Floor Epoxy - Part B

PE700911

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Amber Liquid
Odor	Not available
Odor threshold	Not available
pH	Not available
Melting Point	Not available
Initial Boiling Point / Range	Not available
Flash point	>93°C
Evaporation rate	Not available
Flammability (solid; gas)	Not available
Lower flammable/explosive limit	Not available
Upper flammable/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	0.9 - 1.0
Solubility	Partial
Partition coefficient-n-Octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	Non-reactive
Chemical stability	Stable under recommended handling and storage conditions.
Possibility of hazardous reactions	This product will polymerize if mixed with an epoxy resin. Considerable heat can evolve.
Conditions to avoid	Avoid temperatures exceeding the flash point. Epoxy resins under uncontrolled conditions.
Incompatible materials	Strong oxidizing agents and acids.
Hazardous decomposition products	Unknown

SECTION 11. TOXICOLOGY INFORMATION

Likely Routes of Administration	Inhalation, skin contact, eye contact, ingestion.
Acute Toxicity	Oral: Harmful if swallowed. Dermal: Harmful in contact with skin.
LD50 and LC50 Data	Not available
Skin Corrosion/Irritation	Causes skin irritation.
Serious Eye Damage/ Irritation	Causes serious eye damage.
STOT (Specific Target Organ Toxicity) Single Exposure Inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Aspiration Hazard	Not classified based on available data.
STOT(Specific Target Organ Toxicity) Repeated Exposure	Skin, eyes, central nervous system, respiratory system.
Respiratory and/or Skin Sensitization	No data
Carcinogenicity	Unknown
Chemical name	IARC ACGIH® NTP OSHA
Reproductive Toxicity	Not available
Germ Cell Mutagenicity	Not available
Interactive Effects	Not available

SECTION 12. ECOLOGICAL INFORMATION

Toxic to aquatic life with lasting effects.
This is not required by WHMIS.
This is not required by OSHA HCS 2012.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods
Dispose of contents/container into safe container in accordance with local, regional or national regulations.

SECTION 14. TRANSPORT INFORMATION

UN Number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations:
UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime):
UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III; MARINE POLLUTANT

UN Number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air):
UN3267; CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. Isophorone diamine, 4-nonylphenol, branched); CLASS 8; PG III; MARINE POLLUTANT

SECTION 15. REGULATORY INFORMATION

Not required under Canadian Regulations.



Safety Data Sheet (SDS)
Light Grey #885 Passeport Elite Floor Epoxy - Part B
PE700911

SECTION 16. OTHER INFORMATION

Date of Preparation	August 2020
Date of Last Revision	January 4, 2023
Revision Indicators	The entire MSDS was changed in August 2020 to be in accordance with the WHMIS 2015 which incorporates the Globally Harmonized System of Classification and Labeling of Chemicals for Canadian Workplaces.
References	1. CHOHS Fact Sheets September 2016 ©CCOHS 2016 2. Supplier's Material Safety Data Sheet(s)
ACGIH	American Conference of Governmental Industrial Hygienists
ATE	Acute toxicity estimate
CAS	Chemical Abstract Service
DSL	Domestic Substance List
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods Code
LC	Lethal concentration
LD	Lethal Dosage
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program (U.S.A.)
OSHA	Occupational Safety and Health Administration (U.S.A.)
PEL	Permissible Exposure Limit
STEL	Short-term Exposure Limit
TDG	Transport of dangerous goods in Canada
TLV	Threshold Limit Value
TSCA	Toxic Substances Control Act
TWA	Time Weighted Average
WHMIS	Workplace Hazardous Materials Information System

NOTICE: The facts stated and the recommendations made with respect to the use of this product are based on liable information. No guarantee of accuracy is made. Before using, determine the suitability of the product's intended use. The purchaser assumes all risks and liability for losses, damage, or expenses, directly or indirectly, arising from the handling or use of the product or from any other cause. All recommendations are made on condition that Passeport Élite will not be liable for any damages resulting from its use since Passeport Élite cannot control the conditions under which the product will be transported, stored, handled or used by the purchaser.