



Description:

R20 Graffiti Remover is a biodegradable and safe bio solvent blend. Its composition allows it to remove graffiti made from paint of all kinds as well as permanent pencil inks. R20 graffiti remover can be used on most factory-painted surfaces, anti-graffiti coatings, stone and concrete surfaces with very low porosity and even polished.

Using R20 graffiti remover reduces the risk of injury due to exposure to corrosive or flammable material. Indeed, our product does not contain any acidic or caustic products or aggressive solvents such as methylene chloride.

Technical data:

Physical Condition: Liquid
Colour: Clear
Smell: Fruity
Density: 1.21g/cm³
pH: 6
Melting Point: -15C
Point d'ébullition :205C
Flash Point: > 93.3 oC
Water Solubility: Total
VOCs: 0

Restriction:

Before using R20 graffiti remover, always test a small portion of the coating to be cleaned. This test will be used to determine the compatibility between the paint and the stripper. R20 Graffiti Remover is not designed to remove graffiti from residential paint surfaces such as acrylic paints and alkyl paints. Do not allow to dry on the wall. May damage paintwork as well as some surrounding surfaces. Do not dilute. Do not mix with other products. Do not use on a surface above 30C. Do not use in direct sunlight.

Sampling:

Before starting the total cleaning, test the product on a small hidden area. Leave the product on for a period of 3 to 10 minutes max. Rinse with water. Inspect the surface to determine if the R20 stripper has damaged the surface. To

TECHNICAL SHEET R20

do this, check that the texture of the paint remains the same, that the colour, the gloss or that the finish is not altered. In the event that the R20 stripper has damaged the surface, do not proceed with the total cleaning.

Application:

Following the successful sampling, apply R20 stripper to the entire graffiti using a brush, a bristle roller or a sprayer. Leave the R20 stripper on for a period of 3 to 10 minutes. You can probe the effectiveness of the stripper during the soaking period with a brush using circular motions. Not exceeding 10 minutes, when the graffiti is ready to be removed, you can use a green scouring pad, a cloth, or simply a cold-water pressure machine. Rinse the surface well. If the graffiti is still visible, let the surface dry well and repeat the cleaning steps.

Preventive measure:



Careful! Causes skin irritation. Causes severe eye irritation. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye/face protection. SKIN CONTACT: Wash thoroughly with water. IN CASE OF CONTACT WITH EYES: Rinse carefully with water for several minutes. Remove contact lenses if the victim wears them and if they can be easily removed. Continue to rinse. Specific treatment (see additional first aid instructions on this label). If skin irritation occurs: Consult a physician. If eye irritation persists: Consult a physician. Remove contaminated clothing and wash it before reuse.

Storage:

Protect against frost.

In temperatures between 5C and 30C, as well as in the sealed delivery container, the R20 graffiti remover can be stored for a period of 2 years.

Technical support:

For any additional information, please consult our customer service.

www.opguard.com

The information provided in this datasheet is provided for informational purposes only. We strive to keep this information as accurate and up to date as possible, however, we do not guarantee the accuracy, completeness or suitability of this information. We accept no liability for any direct or indirect loss, harm or damage arising from the use or interpretation of the information provided in this data sheet. Users are encouraged to independently verify all information before using it or making decisions based on it. We reserve the right to change, update or delete any or all of the information contained in this datasheet without notice.

www.opguard.com

450-500-0773

info@opguard.com

4535 avenue thibault, local 6
Saint-hubert, qc, j3y 7n1

OPGUARD