

## OPGUARD

### R30

# GLUE REMOVER

LABEL AND ADHESIVE

NO PETROLEUM SOLVENTS

MILD ODOUR

NON-FLAMMABLE

BIODEGRADABLE

# R30

### Description:

R30 Glue & Adhesive Remover is our latest innovation in plant-based nail polish remover. Indeed, not only does it remove dirt and allow the removal of glues and adhesive, but it does not damage the surface on which it cleans. It is therefore not dangerous for industrial paints, rubber, plastic and vinyl. Another advantage of R30 adhesive remover is that residues do not remain sticky when removing or rinsing it. So, you don't have to worry about overusing the product. It will therefore allow you to clean ecologically, economically and efficiently.

### Benefits:

- Biodegradable
- Petroleum solvent-free
- Uninflammable
- Safe
- Economical
- Safe for the stand
- Low odor
- Rinses easily
- Low VOC
- Plug-and-play/easy to use.

### Technical data:

- Colour: Clear beige
- Smell: low / vegetal / neutral
- pH : 7
- Density: 1.0046g/cm<sup>3</sup>
- VOC: 01.12g/L
- Point d'ébullition : 2000C
- Flash Point: 1200C
- Water Solubility: Partial

### Chemical Nature:

# TECHNICAL SHEET R30

Amalgam of biosolvents

## Conditioning:

Painted: 946ml  
Gallon: 3.78L  
5 gallons: 18.9L

## Application:

R30 Adhesive & Glue Remover is applied to a dry surface. Apply the product to the surface to be cleaned using a brush or a low-pressure sprayer. Leave the product on for at least 20 minutes. After application, probe the surface to be cleaned to determine if the residue to be dissolved is ready to be removed from the substrate. If it seems tough to remove, reapply R30 glue and adhesive remover and leave on for another 20 minutes. Following the second application, remove the residue to be removed using a plastic trowel or a pressure machine. Rinse the surface well. If any residue remains stuck on the substrate, allow to dry, and repeat the applications of R30 glue and adhesive remover. There is no limit to cleaning.

## Precaution:

Always test an inconspicuous part of the substrate before running the full job. Be sure to let the test dry for 7 days in order to determine the compatibility of the B40 glue and bitumen remover. If the product is fully compatible, it should not leave any traces after drying.

Do not apply directly under the sun. Apply in temperatures between 50C and 300C.

Protect surrounding surfaces.

## Consumption:

From 30 to 70 square feet per liter.

The variation in coverage is due to the countless types of glue and adhesive and other product that R30 remover can remove.

## Cleaning of the equipment:

Clean application tools with soapy water.

## Health and safety:



Causes severe eye irritation. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye/face protection. IN CASE OF CONTACT WITH EYES: Rinse carefully with water for several minutes. Remove contact lenses if the victim wears them and if they can be easily removed. Continue to rinse, If eye irritation persists: Consult a physician.

Please refer to the MSDS.

# TECHNICAL SHEET R30

## Technical support:

For any additional information, please consult our customer service.

[www.opguard.com](http://www.opguard.com)

The information provided in this datasheet is provided for informational purposes only. We strive to keep this information as accurate and up-to-date as possible, however, we do not guarantee the accuracy, completeness or suitability of this information. We accept no liability for any direct or indirect loss, harm or damage arising from the use or interpretation of the information provided in this data sheet. Users are encouraged to independently verify all information before using it or making decisions based on it. We reserve the right to change, update or delete any or all of the information contained in this datasheet without notice.

[www.opguard.com](http://www.opguard.com)

450-500-0773

[info@opguard.com](mailto:info@opguard.com)

4535 avenue thibault, local 6

Saint-hubert, qc, j3y 7n1

**OPGUARD**